Rollei **Powerflex 240 HD**

www.rollei.com

Rollei since 1920

24x optical zoom – with a focal length up to 600 millimeters!

- **16 megapixels SONY sensor**
- **3.0“ TFT LCD (7.62 cm)**
- **720p HD video function (1280x720/30 fps)**
- **Voice recording and voice memo for each photo (up to 30 sec)**
- **Automatic and manual shutter speed selection**

24x	16.0	3.0“		720p	24
optical Zoom 25 ~ 600 mm	Megapixels	LCD Panel 7.62 cm	optical Image Stabilizer	HD Video Resolution	Month Warranty and Replacement

Top Details

I like – on facebook.com/rollei

- 40 scene modes, including Night Scene Mode and fisheye
- Fast charging via USB, supports Apple Adaptor (5V/500 mA)
- Adjustable white balance
- Optical image stabilization
- Video: up to 29 minutes recording time
- with built-in speaker and microphone

Technical features

Image sensor	16 Megapixels SONY 1/2.3“ CCD Sensor
Colour	Black and Silver
Resolution	Still Image: 16 MP (4608x3456), 3:2 (4608x3072), 16:9 (4608x2592), 10 MP (3648x2736), 5 MP (2560x1920), 3 MP (2048x1536), VGA (640x480) | Video: 1280x720p/30 fps, 640x480
Objective	Lens construction: 10 groups, 11 elements | Aperture: F = 1:3.0 (W) – 6.9 (T) | f = 4.5 ~ 108 mm, equivalent to 25 ~ 600 mm in 35 mm film format
Focus Range	Normal: wide: 10 cm ~ infinity | Tele: 40 cm ~ infinity Macro wide: 10 ~ 50 cm | Super Macro: 2 ~ 50 cm
Zoom	24x optical zoom
LC-Display	3.0“ LCD Panel (7.62 cm)
ISO	Auto, 64, 100, 200, 400, 800, 1600
Memory Card Slot	for SD up to 4 GB, SDHC up to 32 GB, SDXC > 64 GB
Data format	Still Image: JPEG (EXIF 2.2), DCF 1.0, DPOF | Video: AVI | Sound: WAV
System Requirements	PC: MS Windows XP (SP 2 or later), Vista, Win 7 Mac OS 10.3x ~ 10.6
Connectors	Mini USB 8 PIN | USB 2.0 Full Speed | AV out (NTSC/PAL)
Power	rechargeable Li-Ion battery
Languages	16
Dimensions	106.8 x 68.89 x 40.3 mm
Weight	approx. 220 g (without battery and memory card)

Subject to technical changes.

Black 4 048805 108282

Silver 4 048805 108299